ZXMOTO

500F

SPECIFICATIONS

ENGINE	4 inline-cylinder,DOHC,16-valve,liquid-cooled
DISPLACEMENT	470CC
MAXIMUM POWER	54kW @ 11000 rpm
MAXIMUM TORQUE	48 N·m @ 9500 rpm
COMPRESSION RATIO	12:1
CLUTCH TYPE	Wet multi-plate slipper clutch
FUEL DELIVERY	BOSCH EFI
LENGTH X WIDTH X HEIGHT	2015 × 805 × 1090 mm
WHEELBASE	1395 Mm
SEAT HEIGHT	795 mm
KERB WEIGHT	175 kg
FUEL CAPACITY	15.5 L
STEERING ANGLE	31°
RAKE ANGLE	24.5°
FRONT SUSPENSION	Inverted ϕ 41mm, fully adjustable preload and damping
REAR SUSPENSION	Central monoshock, fully adjustable preload and damping
RIM	Aluminum alloy cast front MT3.5*17 rear MT5.5*17
FRONT BRAKE	300mm dual floating disc 4-Piston opposed caliper (TAISKO)
REAR BRAKE	220mm fixed brake disc, 2-piston opposed caliper (TAISKO™)
FRONT TYRE	CST™ S7 120/70 ZR17
REAR TYRE	CST™ S7 180/55 ZR17
FRAME	Integrated Steel Trellis Diamond Frame

3 YEAR WARRANTY

*ZXMOTO Australia & New Zealand reserves the right to vary colours, specifications and pricing at any time. Please contact your local dealer for final specifications and pricing. In some cases CGI rendered images are used for display purposes.