ZXMOTO

500FL

## SPECIFICATIONS

| | |
|---|---|
| ENGINE | 4 inline-cylinder,DOHC,16-valve,liquid-cooled |
| DISPLACEMENT | 470CC |
| MAXIMUM POWER | <35 kW |
| COMPRESSION RATIO | 12:1 |
| CLUTCH TYPE | Wet multi-plate slipper clutch |
| FUEL DELIVERY | BOSCH EFI |
| LENGTH X WIDTH X HEIGHT | 2015 × 805 × 1090 mm |
| WHEELBASE | 1395 Mm |
| SEAT HEIGHT | 795 mm |
| KERB WEIGHT | 175 kg |
| FUEL CAPACITY | 15.5 L |
| STEERING ANGLE | 31° |
| RAKE ANGLE | 24.5° |
| FRONT SUSPENSION | Inverted ϕ 41mm, fully adjustable preload and damping |
| REAR SUSPENSION | Central monoshock, fully adjustable preload and damping |
| RIM | Aluminum alloy cast front MT3.5*17 rear MT5.5*17 |
| FRONT BRAKE | 300mm dual floating disc 4-Piston opposed caliper (TAISKO) |
| REAR BRAKE | 220mm fixed brake disc, 2-piston opposed caliper (TAISKO™) |
| FRONT TYRE | CST™ S7 120/70 ZR17 |
| REAR TYRE | CST™ S7 180/55 ZR17 |
| FRAME | Integrated Steel Trellis Diamond Frame |

3 YEAR WARRANTY

*ZXMOTO Australia & New Zealand reserves the right to vary colours, specifications and pricing at any time. Please contact your local dealer for final specifications and pricing. In some cases CGI rendered images are used for display purposes.