ZXMOTO

500RR-L

LAMS Approved

SPECIFICATIONS

ENGINE	4 inline-cylinder,DOHC,16-valve,liquid-cooled
DISPLACEMENT	470cc
MAXIMUM POWER	35 kW @ 8000 rpm
MAXIMUM TORQUE	-
COMPRESSION RATIO	12.9:1
CLUTCH TYPE	Wet multi-plate slipper clutch
FUEL DELIVERY	BOSCH EFI
LENGTH X WIDTH X HEIGHT	2005 × 705 × 1125 mm
WHEELBASE	1395 Mm
SEAT HEIGHT	800 mm
KERB WEIGHT	168 kg
FUEL CAPACITY	15 L
STEERING ANGLE	25°
RAKE ANGLE	24.5°
FRONT SUSPENSION	Inverted ϕ 41mm, fully adjustable preload and damping
REAR SUSPENSION	Central monoshock, fully adjustable preload and damping
RIM	Aluminum alloy cast front MT3.5*17 rear MT5.5*17
FRONT BRAKE	300mm dual floating disc 4-Piston opposed caliper (TAISKO)
REAR BRAKE	220mm fixed brake disc, 2-piston opposed caliper (TAISKO™)
FRONT TYRE	CST™ S7 120/70 ZR17
REAR TYRE	CST™ S7 180/55 ZR17
FRAME	Integrated Steel Trellis Diamond Frame
REAR SWINGARM	Single-sided swing arm(aluminum alloy)

3 YEAR WARRANTY

*ZXMOTO Australia reserves the right to vary colours, specifications and pricing at any time. Please contact your local dealer for final specifications and pricing. In some cases CGI rendered images are used for display purposes.