ZXMOTO

MX450

SPECIFICATIONS

ENGINE	Single-cylinder, DOHC, 4-valve, 4-stroke
DISPLACEMENT	449.9cc
MAXIMUM POWER	40 kW @ 9500 rpm
MAXIMUM TORQUE	49 N·m @ 7500 rpm
COMPRESSION RATIO	13.5:1
CLUTCH TYPE	Wet multi-plate slipper hydraulic clutch
FUEL DELIVERY	BOSCH EFI(Dual Fuel Injector)
LENGTH X WIDTH X HEIGHT	2168 × 805 × 1265 mm
WHEELBASE	1485 Mm
SEAT HEIGHT	960 mm
KERB WEIGHT	105 kg
FUEL CAPACITY	6.5 L
RAKE ANGLE	28°
FRONT SUSPENSION	KYB Inverted Fork, Fully Adjustable Damping
REAR SUSPENSION	KYB Rear Shock with External Reservoir, Fully Adjustable Damping
FRONT RIM	21 inch Spoked Wheel
REAR RIM	19 inch Spoked Wheel
FRONT BRAKE	Single Disc 2-Piston Monobloc Caliper
REAR BRAKE	Single Disc 1-piston Monobloc Caliper
FRONT TYRE	90/100-21
REAR TYRE	110/90-19
FRAME	Twin-spar Frame

*ZXMOTO Australia reserves the right to vary colours, specifications and pricing at any time. Please contact your local dealer for final specifications and pricing. In some cases CGI rendered images are used for display purposes.